

## VII. Polypropylene

## As of 01.06.2019

There are no objections to the use of polypropylene in the manufacture of commodities in the sense of § 2, Para. 6, No 1 of the Food and Feed Code (Lebensmittel- und Futtermittelgesetzbuch), provided they are suitable for their intended purpose and the following conditions are met:

1. The use of starting materials for polypropylene is subject to the Commission Regulation (EU) No 10/2011.

*The evaluation presented in the following refers to polymers from the following monomeric starting substances:* 

- a) Monomer: Propylene
- b) Comonomers: Ethylene Butylene 4-Methylpentene 3-Methylbutene b) Comonomers: in total max. 10 %

If butylene is used exclusively as comonomer it may be used up to 12 %, if ethylene is used exclusively as comonomer it may be used up to 15 %.

*The melt flow index (see DIN EN ISO 1133) of the polypropylene must not exceed 100 (2.15 kp, 230 °C) and the melting point of cristallites must not be below 155 °C.* 

- Additives permitted by the Commission Regulation (EU) No 10/2011 may be used in accordance with the restrictions stipulated therein. In addition to these, the raw polymer or finished products may contain only the following production aids<sup>1</sup>, used during manufacture and processing of the polymer, in the maximum amounts given:
  - a) Catalyst residues<sup>2</sup>:

Oxides<sup>3</sup> of calcium, aluminium, silicon, titanium, chromium, vanadium, zirconium and hafnium, in total max. 0.1 %. The finished products must contain no more than 10 ppm chromium, no more than 20 ppm vanadium, no more than 100 ppm zirconium and no more than 100 ppm hafnium.

p-Ethoxybenzoic acid ethyl ester, max. 0.032 %<sup>4</sup>

<sup>&</sup>lt;sup>1</sup> Such production aids include molecular weight regulators which are occasionally used, e.g. bis(tert-butylperoxy-isopropyl)benzene, max. 0.1 %, 2,5-dimethyl-2,5-di-(tert-butylperoxy)hexane, max. 0.1 %, di-tert-butyl peroxide, max. 0.1 %, 3,6,9triethyl-3,6,9-trimethyl-1,2,4,5,7,8-hexoxonane, max. 0.1 % or 3,6,9-trimethyl-3,6,9-tris(ethyl and/or propyl)-1,2,4,5,7,8hexoxonane, max. 0.08 %, tert-butyl peroxyisopropyl carbonate, max. 0.5 %. The surface of commodities made using the above substances must not test positively for peroxides. (see 58th Communication on the testing of plastics, Bundesgesundheitsblatt 40 (1997) 412).

<sup>&</sup>lt;sup>2</sup> Catalysts, as such or in the form of their decomposition products, not contained in the finished product are not considered.

<sup>&</sup>lt;sup>3</sup> Aluminium oxide, calcium oxide, silicon dioxide and titanium dioxide are permitted as additives in accordance with the Commission Regulation (EU) No 10/2011.

<sup>&</sup>lt;sup>4</sup> The residual content of diethyl sulfate in this catalyst must not exceed 10 mg/kg.



Ethylene-bis-(4,5,6,7-tetrahydroindenyl)zirconium dichloride, supported on silica/methylalumoxane support, max. 250 mg/kg polymer

 $Bis(C_{16}-C_{18}-alkyl)$  methylamine, residue in polymer max. 30 mg/kg.

Dichlor(rel-(1R, 1'R)-(dimethylsilylene)-bis-(1,2,3,3a,7a-h)-2-methyl-4-pentyl-1H-indene-1ylidene))zirconium, supported on silica/methyl-alumoxane support, max. 250 mg/kg polymer.

Isopropyl myristate, max. 0.012 %<sup>5, 6</sup>

5-tert-butyl-3-methyl-1,2-benzenediol dibenzoate, the migration of this substance must not exceed 0.05 mg/kg foodstuff or simulant.

- 2',2"'-((((1R,2R)-cyclohexane-1,2-diyl)bis(methylene))bis(oxy))bis(3-(9H-carbazol-9-yl)-5-methyl-[1,1'-biphenyl]-2-ol), the migration of this substance must not exceed 0.05 mg/kg foodstuff or simulant.<sup>6</sup>
- b) Residues of emulsifying agents:

Addition products of ethylene oxide to natural fatty acids, max. 0.2 % or

Nonylphenoxypoly-(ethylenoxy)-ethanol (degree of ethoxylation, 3-14), max. 0.01 %

<sup>&</sup>lt;sup>5</sup> During the polymerisation with a catalyst containing ilsopropyl myristate, the by-product 3-hexadecanol can be formed. Only up to 0.05 mg/kg of this substance may migrate into the foodstuff or food simulant, respectively

<sup>&</sup>lt;sup>6</sup> For the verification of compliance with this recommended migration limit it is feasible to use the fat reduction factor following the conditions defined in annex V of Commission Regulation (EU) No 10/2011.